

SKY VIEW FINANCIAL WETLAND  
CALDWELL COUNTY MISSOURI

T56N, R26W, Section 5

Lat 39.6846611° N

Long 93.8330250° W

WRP PERPETUAL CONTRACT  
NUMBER: 66-6424-11-0143Y

GENERAL TRACT LOCATION



MISSOURI



VICINITY MAP



The excavator is responsible for having all utilities located at the work site or on ingress road prior to beginning work. Call 1-800-DIG-RITE (344-7483) or 811 or click [www.mo1call.com](http://www.mo1call.com). Call 3 days before you dig!


The landowner shall insure that the excavator completes the locate request.

No activities may be taken by contractor that impedes drainage on or from adjacent property owners.

Designed	J.A. Gibson	Date	02-01-2013
Drawn	J.A. Gibson		02-01-2013
Checked	Bruce Embrey		04-01-2013
Approved	<i>[Signature]</i>		04-04-2013

SKY VIEW FINANCIAL WETLAND  
COVER SHEET

United States Department of Agriculture  
Natural Resources Conservation Service

**NRCS**

WETS 4  
727 PCA Rd.  
Warrensburg, MO 64093

File Name
Drawing Name
4/22/13 9:44
Sheet 1 of 11

ESTIMATED QUANTITIES		
DESCRIPTION	QUANTITY	UNIT
Earthfill (Berms)	8460	CY
Earthfill (Spoil areas)	10,570	CY
Earthfill (Habitat Mounds)	4480	CY
12" dia. SDR 35 pvc pipe	125	LF
2' x 12" dia. water control structure	2	EA
18" dia. SDR 35 pvc pipe	68	LF
3' x 18" dia. water control structure	1	EA
Trash rack (Small)	2	EA
Trash rack (Large)	1	EA
Fence post	6	EA
Animal guard (12" dia.)	2	EA
Animal guard (18" dia.)	1	EA
Seedling/cover crop	5.60	AC
* Clearing light-WRP	20.50	AC
+ Clearing medium-WRP	0.50	AC

\* Clearing light-WRP: Includes the cost of all machinery and labor required to clear herbaceous vegetation and scattered seedling trees and shrubs on a per acre basis where a conservation practice will be built. Typically, will involve a small sized rubber tired tractor with a disk or mower. Disk or mower is capable of chopping and distributing the vegetation such that gathering and disposal is not necessary. This item is not applicable to tree planting or herbaceous establishment conservation practices.


TABLE OF CONTENTS	
SHEET #	DESCRIPTION
1	Cover sheet
2	Table of contents/est. quantities
3	General plan map
4A - 4C	Design detail maps
5	Topography map
6	Berm details
7	Spillway details
8	Borrow areas details
9	Habitat mound & spoil area details
10A - 10C	Water control structure details
11A & 11B	Trash rack details

+ Clearing medium-WRP: Includes the cost of all machinery and labor required to clear, grub, gather and dispose of woody encroachment comprising predominately of sapling trees and shrubs. Trees no larger than 4" dbh and scattered herbaceous growth on a per acre basis where a conservation practice will be built. Typically, will involve a medium sized rubber tired tractor or a medium sized tracked equipment with heavy duty disk, blade or shear blade.

Date	
Designed	J.A. Gibson 02-01-2013
Drawn	J.A. Gibson 02-01-2013
Checked	Bruce Embrey 04-01-2013
Approved	J.A. Gibson 04-04-2013

SKY VIEW FINANCIAL WETLAND  
TABLE OF CONTENTS/EST. QUANTITIES

United States Department of Agriculture



NRCS

Natural Resources Conservation Service

WETS 4  
727 PCA Rd.  
Warrensburg, MO 64093



**Benchmark Descriptions:**

TBM #1: EL. = 745.23 on top of aluminum disk  
easement marker #13 at the Northwest corner  
of 1/2 easement 60 ft. West of centerline Catawba Rd.  
X = 1,406,017.4690 ft.  
Y = 14,415,372.7400 ft.

TBM #2: EL. = 742.65 on top of aluminum disk  
easement marker #15 940 ft. South of TBM #1.  
X = 1,406,016.3640 ft.  
Y = 14,414,432.2400 ft.

TBM #3: EL. = 742.30 on top of aluminum disk  
easement marker #16 470 ft. South of TBM #3.  
X = 1,406,015.8390 ft.  
Y = 14,413,961.8800 ft.

TBM #4: EL. = 743.49 on top of aluminum disk  
easement marker #18 at the Southeast corner  
of the easement.  
X = 1,406,015.5500 ft.  
Y = 14,413,051.2700 ft.

TBM #5: EL. = 743.38 on top of aluminum disk  
easement marker #20 875 ft. West of TBM #4.  
X = 1,405,143.8050 ft.  
Y = 14,413,076.9100 ft.

TBM #6: EL. = 745.89 on top of aluminum disk  
easement marker #2 in the West easement line  
565 ft. Northeast of centerline of Ironwood Rd.  
X = 1,403,719.7710 ft.  
Y = 14,413,617.4000 ft.

TBM #7: EL. = 753.40 on top of aluminum disk  
easement marker #4 875 ft. Northeast of TBM #6.  
X = 1,403,929.9130 ft.  
Y = 14,414,470.9500 ft.

**Pool Information:**

Berms #1 - #3: 27.0 acres of saturation at EL. = 743.5  
after excavation.


Berms #4 - #6: 13.5 acres of saturation at EL. = 743.5  
after excavation.

Berm #7: 9.8 acres of saturation at EL. = 743.5  
after excavation.




Date	02-01-2013
Designed	J.A. Gibson
Drawn	J.A. Gibson
Checked	Bruce Embrey
Approved	J.A. Gibson

**SKY VIEW FINANCIAL WETLAND  
GENERAL PLAN MAP**






# Southeast field



Date		02-01-2013
Designed	J.A. Gibson	02-01-2013
Drawn	J.A. Gibson	02-01-2013
Checked	Bruce Embrey	04-01-2013
Approved	J.A. Gibson	04-04-2013
SKY VIEW FINANCIAL WETLAND DESIGN DETAIL MAP		
 NRCS Natural Resources Conservation Service United States Department of Agriculture		
File Name		
Drawing Name		
Sheet 4A of 11		

North field



Designed	J.A. Gibson	02-01-2013
Drawn	J.A. Gibson	02-01-2013
Checked	Bruce Embrey	04-01-2013
Approved	J.A. Gibson	04-04-2013


SKY VIEW FINANCIAL WETLAND  
DESIGN DETAIL MAP



File Name

Drawing Name

# Southwest field



Designed	J.A. Gibson	02-01-2013
Drawn	J.A. Gibson	02-01-2013
Checked	Bruce Embrey	04-01-2013
Approved	J.A. Gibson	04-04-2013

## SKY VIEW FINANCIAL WETLAND DESIGN DETAIL MAP




File Name

Drawing Name

Sheet 4C of 11





SKY VIEW FINANCIAL WETLAND  
TOPOGRAPHY MAP


Designed	J.A. Gibson	Date	02-01-2013
Drawn	J.A. Gibson		02-01-2013
Checked	Bruce Embrey		04-01-2013
Approved	J.A. Gibson		04-04-2013



NOTES:

1. The centerline of the berms will be flagged by NRCS. The contractor will be responsible for staking the toes of the slopes.
2. Strip all areas where the berms will be built before placing fill.
3. Fill material for the berms will only be taken from borrow areas as shown on sheets 4A - 4C of 11 and to designated depths.
4. All fill material must be clean of vegetation and/or rooty material. NRCS will reject fill material that contains inordinate amounts of vegetation.
5. Earthfill shall be placed in horizontal layers not to exceed 8" in thickness. Each layer shall be compacted by two (2) complete passes of the loaded scrapper or sheep foot.
6. The berms will be seeded. See attached NRCS's seeding requirements.

BERM SUMMARY						
NAME	YARDAGE cu.yds.	SEEDED AREA ac.	TOP ELEVATION	TOP WIDTH ft.	LENGTH ft.	SIDE SLOPES
Berm #1	1840	1.30	744.2	10	1651	10:1
Berm #2	770	0.30	744.2	10	241	10:1
Berm #3	1260	1.20	744.2	10	1924	10:1
Berm #4	1070	0.70	744.2	10	916	10:1
Berm #5	610	0.30	744.2	10	276	10:1
Berm #6	450	0.30	744.2	10	387	10:1
Berm #7	2460	1.50	744.2	10	1750	10:1
Totals:	8460	5.60				



DETAIL "A"

Berms #1, #4, & #6 x-sect.

Berm #2 x-sect.  
Sta. 0+00 - Sta. 1+00  
Sta. 1+50 - Sta. 2+41

Berm #3 x-sect.  
Sta. 0+00 - Sta. 13+20  
Sta. 14+20 - Sta. 19+24

Berm #5 x-sect.  
Sta. 0+00 - Sta. 0+85  
Sta. 1+25 - Sta. 2+76

Berm #7 x-sect.  
Sta. 0+00 - Sta. 4+95  
Sta. 5+95 - Sta. 17+50

Date  
Designed J.A. Gibson 02-01-2013  
Drawn J.A. Gibson 02-01-2013  
Checked Bruce Embrey 04-01-2013  
Approved J.A. Gibson 04-04-2013

SKY VIEW FINANCIAL WETLAND  
BERM DETAILS



File Name  
Drawing Name  
4/22/13 9:44  
Sheet 6 of 11

NOT TO SCALE









# NOTES:

1. The centerline of spillway #1 will be flagged by NRCS. The contractor will be responsible for staking the top width and toes of the slopes.
2. Strip the area where spillway #1 will be built before placing fill.
3. Construct spillway #1 exactly as shown below.
4. All fill material must be clean of vegetation and/or rooty material. NRCS will reject fill material that contains inordinate amounts of vegetation.

5. Fill material for spillway #1 will only be taken from borrow areas as shown on sheet 4A of 11 and to designated depths.
6. Earthfill shall be placed in horizontal layers not to exceed 6' in thickness. Each layer shall be compacted by two (2) complete passes of the loaded scrapper or sheep foot.


7. The perimeter of spillways #2 & #3 will be flagged by NRCS. The contractor will be responsible for staking the toes of the slopes.
8. Cut spillways #2 & #3 down to the exact elevation and dimensions shown.
9. The spillways will be seeded. See attached NRCS's seeding requirements.



NOT TO SCALE

Designed	J.A. Gibson	Date	02-01-2013
Drawn	J.A. Gibson		02-01-2013
Checked	Bruce Embrey		04-01-2013
Approved	J.A. Gibson		04-04-2013

## SKY VIEW FINANCIAL WETLAND SPILLWAY DETAILS




File Name
Drawing Name
4/22/13 9:44
Sheet 7 of 11

# NOTES:

1. The borrow areas shown on sheets 4A - 4C of 11 are the only allowable areas for excavation.
2. Perimeter of borrow areas will be flagged in the field by NRCS. The contractor will be responsible for staking the toes of the slopes.
3. Strip borrow areas before removing fill.
4. All fill material for berms must be clean of vegetation and/or rooty material. NRCS will reject fill material that contains inordinate amounts of vegetation.
5. Stripped material can be placed in spoil areas and habitat mounds.
6. No borrow shall be taken within 30' of either toe of the berms unless shown on sheets 4A - 4C of 11.

7. If a permeable area is encountered, the contractor will stop excavation immediately. A minimum of 12' compacted impermeable material will be replaced over this area. The contractor will contact NRCS for instructions for moving to a new area to continue borrowing for fill.
8. Excavated materials from the borrow areas will go to the location designated in the chart below.
9. If the borrow areas have been excavated as laid out and to the design requirements and additional construction material is still needed to complete the project, contact NRCS WETS team for instructions.
10. As soon as all the berms, spoil areas & habitat mounds have been completed as laid out and to design requirements, immediately stop excavating material from the borrow areas.



BORROW AREA SUMMARY					
NAME	APPROX. YARDAGE cu.yds.	BOTTOM ELEVATION	CLEARING AC.	SIDE SLOPES	* LOCATION FOR EXCAVATED MATERIAL
Borrow area #1	12,240	742	7.50	4:1	Berms #1 & #3 Spoil areas #1 - #3 & Hab. md. #1 - #3
Borrow area #2	1640	741.5	1.10	4:1	Berm #2 Spoil areas #2, #3 & #5
Borrow area #3	3150	740.6	1.20	4:1	Berms #5 & #6 Spoil areas #5 & #6
Borrow area #4	3310	742.3	2.20	4:1	Berm #4 Spoil area #4 & Hab. md. #4
Borrow area #5	1170	742	0.70	4:1	Berm #6 Hab. md. #5
Borrow area #6	4400	742.3	2.70	4:1	Berm #7 Spoil area #7 & Hab. mds. #6 & #7
TOTALS:	25,910		15.40		

\*NOTE: Contractor may rearrange locations for excavated material if in his opinion it would save him time and/or expenses.

NOT TO SCALE:

## SKY VIEW FINANCIAL WETLAND BORROW AREA DETAILS

Designed J.A. Gibson 02-01-2013  
Drawn J.A. Gibson 02-01-2013  
Checked Bruce Embrey 04-01-2013  
Approved J.A. Gibson 04-04-2013



United States Department of Agriculture  
Natural Resources Conservation Service  
**NRCS**  
WETS 4  
727 PCA, Rd.  
Warrensburg, MO 64093

File Name  
Drawing Name  
4/22/13 9:44  
Sheet 8 of 11



NOTES:

1. The perimeter of the habitat mounds will be flagged by NRCS. The contractor will be responsible for staking the toes of the slopes.
2. Do not strip the areas where the habitat mounds will be built before placing fill.
3. Fill material for the habitat mounds will only be taken from borrow areas as shown on sheets 4A - 4C of 11 and to designated depths.
4. Habitat mounds must be smooth enough to allow owner to bush hog with standard equipment.
5. Do not seed the habitat mounds.





HABITAT MOUND SUMMARY						
NAME	YARDAGE cu.yds.	SEEDED AREA ac.	TOP ELEVATION	TOP WIDTH ft.	LENGTH ft.	SIDE SLOPES
Habitat md. #1	1090	N/A	744	varies	varies	4:1
Habitat md. #2	610	N/A	744	varies	varies	4:1
Habitat md. #3	730	N/A	744	varies	varies	4:1
Habitat md. #4	690	N/A	744	varies	varies	4:1
Habitat md. #5	510	N/A	744	varies	varies	4:1
Habitat md. #6	350	N/A	744.5	varies	varies	4:1
Habitat md. #7	500	N/A	744.5	varies	varies	4:1
Total:	4480					


(Not to Scale)

NOTES:

1. The perimeter of the spoil areas will be flagged by NRCS. The contractor will be responsible for staking the toes of the slopes.
2. Do not strip the areas where the spoil areas will be built before placing fill.
3. Fill material for the spoil areas will only be taken from borrow areas as shown on sheets 4A - 4C of 11 and to designated depths.
4. Spoil areas must be smooth enough to allow owner to bush hog with standard equipment.
5. Do not seed the spoil areas.



SPOIL AREA SUMMARY						
NAME	YARDAGE cu.yds.	SEEDED AREA ac.	TOP ELEVATION	TOP WIDTH ft.	LENGTH ft.	SIDE SLOPES
Spoil area. #1	2330	N/A	745.2	N/A	N/A	4:1
Spoil area. #2	1450	N/A	745.2	N/A	N/A	10:1
Spoil area. #3	2060	N/A	745.2	N/A	N/A	10:1
Spoil area. #4	950	N/A	745.2	N/A	N/A	4:1
Spoil area. #5	1660	N/A	745.2	N/A	N/A	4:1
Spoil area. #6	1400	N/A	745.2	N/A	N/A	4:1
Spoil area. #7	410	N/A	745.2	N/A	N/A	4:1
Spoil area. #8	310	N/A	744.2	N/A	N/A	4:1
Total:	10,570					



(Not to Scale)

Designed J.A. Gibson 02-01-2013  
Drawn J.A. Gibson 02-01-2013  
Checked Bruce Embrey 04-01-2013  
Approved J.A. Gibson 04-04-2013

SKY VIEW FINANCIAL WETLAND  
HABITAT MOUND & SPOIL AREA DETAILS



File Name



Drawing Name

4/22/13 9:44

Sheet 9 of 11

1. Water control structure #1 will be a 3' tall (min. 22.5' weir length) Agri-Drain, ADS or equivalent inline water level control structure and 68' of 18" dia. SDR 35 pvc pipe conforming to ASTM D3034 or PS46 pvc pipe conforming to ASTM F679.
2. ALL pipe joints and structure connections must be water tight. The contractor shall be fully responsible for any and all work required to correct leakage.
3. Locate any short sections of pipe immediately adjacent to the structure.
4. Fence posts are needed to both identify the location and protect the water control structure's riser.
5. Fill around water control structure's riser WILL be approximately 0.5' below the top of the riser.

6. Rubber tire, hand or manually directed power tamper will be used on backfill around all pipes and structures. Water packing will be allowed.
7. Construct a smooth and maintainable transition from this reach to adjacent reaches.
8. Inspection by NRCS of water control structure and pipes is required. Contractor must give 24 hours notice before work on water control structure begins.
9. Contractor will spray with red paint a line at EL. = 743.5 on inside of WCS to show the maximum water level.
10. May have to trim the top board to achieve the correct water line elevation in the water control structure.



	Date
Designed <u>J.A. Gibson</u>	<u>02-01-2013</u>
Drawn <u>J.A. Gibson</u>	<u>02-01-2013</u>
Checked <u>Bruce Embrey</u>	<u>04-01-2013</u>
Approved <u>J.A. Gibson</u>	<u>04-04-2013</u>



SKY VIEW FINANCIAL WETLAND  
WATER CONTROL STRUCTURE DETAILS



# NOTES:

1. Water control structure #2 will be a 2' tall (min. 14" weir length) Agri-Drain, ADS or equivalent inline water level control structure and 62' of 12" dia. SDR 35 pvc pipe conforming to ASTM D3034.
2. ALL pipe joints and structure connections must be water tight. The contractor shall be fully responsible for any and all work required to correct leakage.
3. Locate any short sections of pipe immediately adjacent to the structure.
4. Fence posts are needed to both identify the location and protect the water control structure's riser.
5. Fill around water control structure's riser WILL be approximately 0.5' below the top of the riser.


6. Rubber tire, hand or manually directed power tamper will be used on backfill around all pipes and structures. Water packing will be allowed.
7. Construct a smooth and maintainable transition from this reach to adjacent reaches.
8. Inspection by NRCS of water control structure and pipes is required. Contractor must give 24 hours notice before work on water control structure begins.
9. Contractor will spray with red paint a line at EL. = 743.5 on inside of WCS to show the maximum water level.
10. May have to trim the top board to achieve the correct water line elevation in the water control structure.



NOT TO SCALE:

Date	Designed	Drawn	Checked	Approved
02-01-2013	J.A. Gibson	J.A. Gibson	Bruce Embrey	J.A. Gibson
02-01-2013				
04-01-2013				
04-04-2013				

## SKY VIEW FINANCIAL WETLAND WATER CONTROL STRUCTURE DETAILS





File Name
Drawing Name
4/22/13 9:44
Sheet 10B of 11

# NOTES:

1. Water control structure #3 will be a 2' tall (min. 14" weir length) Agri-Drain, ADS or equivalent inline water level control structure and 63' of 12" dia. SDR 35 pvc pipe conforming to ASTM D3034.
2. ALL pipe joints and structure connections must be water tight. The contractor shall be fully responsible for any and all work required to correct leakage.
3. Locate any short sections of pipe immediately adjacent to the structure.
4. Fence posts are needed to both identify the location and protect the water control structure's riser.
5. Fill around water control structure's riser WILL be approximately 0.5' below the top of the riser.


6. Rubber tire, hand or manually directed power tamper will be used on backfill around all pipes and structures. Water packing will be allowed.
7. Construct a smooth and maintainable transition from this reach to adjacent reaches.
8. Inspection by NRCS of water control structure and pipes is required. Contractor must give 24 hours notice before work on water control structure begins.
9. Contractor will spray with red paint a line at EL. = 743.5 on inside of WCS to show the maximum water level.
10. May have to trim the top board to achieve the correct water line elevation in the water control structure.



NOT TO SCALE:

Date	02-01-2013
Designed	J.A. Gibson
Drawn	J.A. Gibson
Checked	Bruce Embrey
Approved	J.A. Gibson

## SKY VIEW FINANCIAL WETLAND WATER CONTROL STRUCTURE DETAILS



File Name	
Drawing Name	
4/22/13 9:44	




Date  
 Designed J.A. Gibson 02-01-2013  
 Drawn J.A. Gibson 02-01-2013  
 Checked Bruce Embrey 04-01-2013  
 Approved J.A. Gibson 04-04-2013

SKY VIEW FINANCIAL WETLAND  
 TRASH RACK DETAILS




File Name  
 Drawing Name


BILL OF MATERIALS			
MARK	QUAN	DESCRIPTION	LENGTH
1	2	5" Dia. Wood Post - Pressure Treated	7'-0"
2	1	5" Dia. Wood Post - Pressure Treated	8'-0"
3	4	2"x 6" Wood Brace - Pressure Treated	8'-0"
4	6	3/8" Bolt w/nut & washers (Galv or paint w/asphaltic materials)	
5	6	2"x6" Collar - Pressure Treated (optional for 3/8" bolts)	
		16d common Nails - Hot Dipped Galvanized or Stainless steel	
		Wire Staples - Hot Dipped Galvanized or Stainless steel	1 1/4"
6	4	Feedlot Panels - Min. 36" High	8'-0"



PLAN




SIDE ELEVATION



STANDARD

DETAIL "H1" OPTIONAL




POST ANCHORAGE


- NOTES:**
1. Minimum height of hog panel to be 34" or 52" for cattle panel. The minimum length of Mark 1 posts to be 7' for hog panel and 8 1/2' for cattle panel.
  2. The feedlot panels shall be fastened to each post and brace with 2 strands per loop of 10 gage insulated copper wire securely twisted. Insulation can be THHN or THWN. Spacing of wire loops shall not exceed 2 feet with minimum 2 loops per post and 5 loops per brace.
  3. Panels shall be 1/4" galvanized steel rods welded together to form a panel. Maximum spacing of rods shall be 6 inches vertical and 8 inches horizontal.
  4. Panels placed across top shall be securely fastened together as shown in Note 2. Trim panels to fit.
  5. This detail shall only be used on low head, low velocity wetland pipes.
  6. Trim Mark 3 top brace as needed. Nail to top of other Mark 3 braces.
  7. Bronzed 3" long deck screws may be used in lieu of galvanized 16d common nails.

(LARGE)

NOT TO SCALE:



PLAN




SIDE ELEVATION


BILL OF MATERIALS (EACH)			
MARK	QUAN	DESCRIPTION	LENGTH
1	3	Metal T-Post	min 5 1/2'
2	4	Panels - Min. 34" high	4'-0"
3	---	Wire Loops (as needed)	

NOTES:

1. Minimum height of hog panel to be 34" or 52" for cattle panel. The minimum length of Mark 1 posts to be 5 1/2' for hog panel and 7' for cattle panel.
2. The feedlot panels shall be fastened to each post with 2 strands per loop of 10 gage insulated copper wire securely twisted. Insulation can be THHN or THWN. Spacing of wire loops shall not exceed 2' with minimum 2 loops per post.
3. Panels shall be 1/4" galvanized steel rods welded together to form a panel. Maximum spacing of rods shall be 6" vertical and 8" horizontal.
4. Panels placed across top shall be securely fastened together as described in Note 2 and trimmed to fit.
5. This trash rack detail shall only be used on low head, low velocity wetland pipes.



DETAIL "H2"



POST ANCHORAGE

(SMALL)



2010 2011 2012 2013 2014

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1

© 2011 Pearson Education, Inc. All rights reserved. Printed in the United States of America. This publication is protected by copyright. Any unauthorized reproduction or distribution, in any form or by any means, without written permission from Pearson Education, Inc., is prohibited. All trademarks are the property of their respective owners.

[Home](#)
[About](#)
[Blog](#)
[Contact](#)
[Feedback](#)

